

GO PT

3G/4G PT Battery Powered Security Camera



Specifications

Video & Audio

Image Sensor

Starlight CMOS Image Sensor

Video Resolution

1080p HD at 15 frames/sec

Video Format

H.264

Lens

Fixed lens, f=4mm Fixed, F-2.0, With IRCUT

Field of View

105° diagonal

Pan/Tilt Angle

- Horizontal: 355°
- Vertical: 140°

Night Vision

Up to 10 m (33 ft)

Digital Zoom

6x digital zoom

Audio

High-quality speaker and microphone



PIR Detection & Alerts

PIR Detecting Distance

Adjustable up to 10m (33ft)

PIR Detecting Angle

90° horizontal

Audio Alert

Customized voice-recordable alerts

Other Alerts

Instant email alerts and push notifications

3G/ 4G Bandwidth

Frequency Bands

Europe

LTE FDD: B1/B3/B5/B7/B8/B20

WCDMA: B1/B5/B8

Transmission Data

LTE FDD: Max 10Mbps (DL), Max 5Mbps (UL)

LTE TDD: Max 8.96Mbps (DL), Max 3.1Mbps (UL)

HSPA+: Max 42Mbps (DL), Max 5.76Mbps (UL)

UMTS: Max 384Kbps (DL), Max 384Kbps (UL)

Power

Battery

6500mAh rechargeable battery (Battery life varies based on settings, usage & temperature)

Solar

Can be powered by Reolink Solar Panel

DC Power

Can be powered by 5V/2A USB power adaptor

Storage

Local Storage

Supports up to 64GB micro SD card

Cloud Storage

Supports Reolink Cloud



Working Environment

Operating Temperature

-10° to 55° C (14° to 131° F)

Weather resistance

IP65 certified weatherproof

Size & Weight

Size

Ø98 x 112mm

Weight (Battery included)

485 g (17.1 oz)