

A3 (V7) Splicer

CLAD ALIGNMENT ARC FUSION SPLICER

- New Friendly GUI Design
- SOC Support
- 4.3" Color LCD Touch Screen
- Portable Charger Support



DETAILED VIEW



TECHNICAL SPECIFICATIONS

Model	A3
Alignment Method	Clad Alignment (4 Motors)
Number of Fiber	Single
Applicable Fibers	SM (ITU-T G.652&G.657) / MM (ITU-T G.651) / DS (ITU-T G.653) / NZDS (ITU-T G.655)
Cladding Diameter	80 ~ 150µm
Cleaved Length	Diameter: 0.125mm ~ 1mm (coating) / Cleave Length 5 ~ 16mm
Typical Splice Loss	SM: 0.03dB / MM: 0.01dB / DS: 0.05dB / NZDS: 0.05dB / G.657: 0.03dB (Measured by fusion splicing compensating cutback according to ITU-T standard)
Return Loss	>> 60dB
Estimated Splice Loss	Available
Splice Time	Quick mode 7s
Splice Mode	Preset 6 kinds of splicing mode, Max 320 mode available
Heating Sleeve	20 ~ 60mm
Heating Time	15s (45mm, slim 60mm), 20s (60mm)
Heating Mode	Max 32modes
Pull Test	1.96 ~ 2.25N
Dimension	197W x 137D x 87H mm (including rubber bumper) / 187W x 128D x 82H mm (excluding rubber bumper)
Weight	1.206kg (with battery) / 0.997kg (without battery)
White LED	2 White LEDs
Monitor	4.3" Color LCD display, Full touch screen
Fiber View	X, Y, X/Y
Magnification	120 ~ 240x
Results Storage	10,000 Splice data / 10,000 Splice image
Power Supply	AC Input 100 ~ 240V, DC Input 9 ~ 14V
Terminal	USB Type C
Battery Capacity	3000mAh Battery Capacity, Typical 150 cycles (Splice+Heat), Power save mode 200 cycles (Splice+Heat)
Electrode Life	5500 arcs discharges

PACKAGE LIST Standard Package

Model / Part No.	Description
	Main Unit
A3	Fusion Splicer
	Standard Accessories
V7	Cleaver 1ea
FH-45	Fiber Holder 1set
FH-SOC-L	SOC Fiber Holder 1ea
HTS-SOC-05	SOC Heater Cover 1ea
JS-1618	AC Adapter 1ea
CG-22	Cooling Tray 1ea
E-50	Electrode 1set
LBT-3000-02	Battery Pack (3000mAh) 1ea
ACC-25	Power Cable 1ea
USB-8P	USB Cable 1ea
USB-9P	USB Cable 1ea
ICC-54	Carrying case 1ea
IWS-05	Work Station for A2, A3 1ea
ST-01	Shoulder Strap (Carrying Case) 2ea
	Quick Reference 1ea

PACKAGE LIST Optional Accessories

Model / Part No.	Description	
TK02-AP01	Alcohol Pump	1ea
TK02-MP01	Stripper	1ea
EG-18	Electrode Grinder	1ea
PS-60S	Heating Sleeve (60mm)	1pack (100ea)

ENVIRONMENTAL CONDITION & TEST

Items	Specifications
Operating Condition	Altitude: 0 ~ 5000m Humidity: 0 ~ 95%, non-dew Temperature: -10 ~ 50 °C Wind: up to 15m/sec
Storage Condition	Humidity: 0 ~ 95%, non-dew Temperature: -20 ~ 60 °C
Resistance Tests	Shock Resistance : 76cm for bottom surface drop Exposure to Dust : 0.1 to 500um diameter aluminium silicate Rain Resistance : 10 mm/h for 10 mins

- Water resistance (IPx2)



- Shock resistance (Drop from 76cm)



- Dust resistance (IP5X)



* We do not guarantee and are not responsible for any damage caused due to tampering of the product under above conditions.

* USB-8P Type-C USB to Type-A USB (Male) Cable

* USB-9P Type-C USB to Type-A USB (Female) Cable

The Information on this catalog is subject to change without prior notice.